

Nokian European

Nokian NTR 45

Sizes 295/80 R 22.5
315/70 R 22.5
315/80 R 22.5

Application All-season drive axle tyre

- Medium and long distance haul
- Busses and trucks



Maximum load capacities per axle

Size	Pattern Design	LI/SS	Inflation Pressure	Single Load	Dual Load
295/80R22.5	NTR 45	152/148M	8,50 bar	7100 kg @ 130 km/h	12600 kg @ 130 km/h
315/70R22.5	NTR 45	154/150L	9,00 bar	7500 kg @ 120 km/h	13400 kg @ 120 km/h
		152/148M	8,50 bar	7100 kg @ 130 km/h	12600 kg @ 130 km/h
315/80R22.5	NTR 45	154/150M	8,25 bar	7500 kg @ 130 km/h	13400 kg @ 130 km/h
		156/150L	8,50 bar	8000 kg @ 120 km/h	13400 kg @ 120 km/h
			8,25 bar		

Tyre dimensions

Size	Pattern Design	Tread depth (mm)	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Minimum Dual Spacing (mm)
295/80R22.5	NTR 45	20,0	9.00 , 8.25	1049	300	487	3169	335
315/70R22.5	NTR 45	19,5	9.00 , 9.75	1014	312	467	3075	351
315/80R22.5	NTR 45	20,0	9.00 , 9.75	1080	314	499	3256	351

Compound Special compound for All-season use

Properties

- Excellent mileage
- Even tyre wear
- Open pattern provides good grip
- M+S marking
- Driving Safety Indicators (DSI)

Certificates

- E4-54R-0016901 (295/80 R 22.5)
- E4-54R-0016902 (315/70 R 22.5)
- E4-54R-0016903 (315/80 R 22.5)
- E4-117R-010436-S (Noise homologation)

4.7.2008