

Nokian European

Nokian NTR 68

Sizes 13 R 22.5
315/80 R 22.5

Application All-season on/off drive axle tyre

- For severe conditions



Maximum load capacities per axle

| Size | Pattern Design | LI/SS | Inflation Pressure | Single Load | Dual Load |
|-------------|----------------|----------------------|----------------------|---|---|
| 13R22.5 | NTR 68 | 154/150K 156/150G | 7,90 bar 7,90 bar | 3750 kg @ 110 km/h 4000 kg @ 90 km/h | 6700 kg @ 110 km/h 6700 kg @ 90 km/h |
| 315/80R22.5 | NTR 68 | 156/150K | 8,30 bar | 4000 kg @ 110 km/h | 6700 kg @ 110 km/h |

Tyre dimensions

| Size | Pattern Design | Tread depth (mm) | Approved Rims (in) | Overall Diameter (mm) | Tyre Width (mm) | Static Loaded Radius (mm) | Rolling Circ. (mm) | Minimum Dual Spacing (mm) |
|-------------|----------------|------------------|--------------------|-----------------------|-----------------|---------------------------|--------------------|---------------------------|
| 13R22.5 | NTR 68 | 20,0 | 9.00 , 9.75 | 1124 | 328 | 524,4 | 3432,5 | 350 |
| 315/80R22.5 | NTR 68 | 20,0 | 9.00 , 9.75 | 1081 | 312 | 497,8 | 3296,8 | 351 |

Compound Special cut and crack resistant compound for All-season use

Properties

- Low heat build-up
- Good self-cleaning and grip due to open pattern design
- M+S marking
- Driving Safety Indicators (DSI)

Certificates

- E4-54R-0018792 (13 R 22.5)
- E4-54R-0018793 (315/80 R 22.5)
- E7-117R-010906-S (Noise homologation)

17.6.2009