

Tyre size	Pattern design	Load Index Speed Symbol	Additional marking	Fitting Single/ Dual	Speed symbol	Reference speed (km/h)	Maximum load capacity per axle (kg) at various cold inflation pressures (bar) 1)																		
							5,00	5,25	5,50	5,75	6,00	6,25	6,50	6,75	7,00	7,25	7,50	7,75	8,00	8,25	8,50	8,75	9,00		
							2530	2640	2750	2860	2960	3070	3180	3290	3400										
215/75R17.5	NOKIAN NTR 32 NOKAIN NTR 45	126/124M 126/124M	-	S	M	130																			
				D	M	130	4760	4960	5170	5370	5580	5780	5990	6190	6400										
215/75R17.5	NOKIAN NTR 72	135/133J	-	S	M	100					3190	3300	3420	3540	3660	3770	3890	4010	4130	4240	4360				
				D	M	100					6020	6250	6470	6690	6910	7130	7350	7570	7800	8020	8240				
235/75R17.5	NOKIAN NTR 32 NOKIAN NTR 45	132/130M 132/130M	-	S	M	130			2950	3060	3180	3300	3420	3530	3650	3770	3880	4000							
				D	M	130			5600	5820	6040	6270	6490	6710	6930	7150	7380	7600							
235/75R17.5	NOKIAN NTR 72	143/141J	-	S	M	100					3880	4020	4170	4310	4450	4590	4740	4880	5020	5160	5310	5450			
				D	M	100					7330	7600	7870	8140	8410	8680	8950	9220	9490	9760	10030	10300			
265/70R19.5	NOKIAN NTR 72	140/138M	-	S	J	130			3680	3830	3980	4120	4270	4410	4560	4710	4850	5000							
				D	J	130			6960	7230	7510	7780	8060	8340	8610	8890	9160	9440							
265/70R19.5	NORDMAN NTR 72 NORDMAN NTR 73	143/141J 143/141J	-	S	J	130					3980	4130	4280	4420	4570	4720	4860	5010	5160	5300	5450				
				D	J	130					7530	7810	8090	8360	8640	8920	9190	9470	9750	10020	10300				
275/70R22.5	NOKIAN NTR 32	148/145M	-	S	M	130					4370	4530	4690	4850	5010	5170	5340	5500	5660	5820	5980	6140	6300		
				D	M	130					8050	8350	8640	8940	9230	9530	9830	10120	10420	10710	11010	11310	11600		
295/80R22.5	NOKIAN NTR 32 NOKIAN NTR 45	152/148M 152/148M	-	S	M	130					5190	5380	5570	5760	5950	6150	6340	6530	6720	6910	7100				
				D	M	130					9210	9550	9890	10230	10570	10910	11240	11580	11920	12260	12600				
315/70R22.5	NOKIAN NTR 32 NOKIAN NTR 45	154/150L 154/150L	152/148M 152/148M	S	L	120					5200	5390	5590	5780	5970	6160	6350	6540	6730	6930	7120	7310	7500		
				D	L	120					9300	9640	9980	10320	10660	11010	11350	11690	12030	12370	12720	13060	13400		
				S	M	130							5190	5380	5570	5760	5950	6150	6340	6530	6720	6910	7100		
				D	M	130						9210	9550	9890	10230	10570	10910	11240	11580	11920	12260	12600			
315/80R22.5	NOKIAN NTR 32 NOKIAN NTR 45	154/150M 154/150M	156/150L 156/150L	S	M	130					5640	5840	6050	6260	6460	6670	6880	7090	7290	7500					
				D	M	130					10070	10440	10810	11180	11550	11920	12290	12660	13030	13400					
				S	L	120							5850	6060	6280	6490	6710	6920	7140	7350	7570	7780	8000		
				D	L	120						10070	10440	10810	11180	11550	11920	12290	12660	13030	13400				
315/80R22.5	NOKIAN NTR 46 NOKIAN NTR 68	156/150K 156/150K	-	S	K	110					6010	6230	6450	6670	6890	7120	7340	7560	7780	8000					
				D	K	110					10070	10440	10810	11180	11550	11920	12290	12660	13030	13400					
385/55R22.5	NOKIAN NTR 72S	160K	158L	S	K	110					6250	6470	6700	6930	7160	7390	7620	7850	8080	8310	8540	8770	9000		
				S	L	120							6210	6440	6670	6900	7130	7350	7580	7810	8040	8270	8500		
385/65R22.5	NOKIAN NTR 72S NOKIAN NTR 73S	158L	160K	S	L	120					6220	6440	6670	6900	7130	7360	7590	7810	8040	8270	8500				
				S	K	110							6240	6470	6700	6930	7160	7390	7620	7850	8080	8310	8540	8770	9000
13R22.5	NOKIAN NTR 68	154/150K	156/150G	S	K	110								6220	6430	6650	6860	7070	7290	7500					
				D	K	110										11110	11500	11880	12260	12640	13020	13400			
				S	G	90											6280	6490	6710	6920	7140	7350	7570	7780	8000
				D	G	90											11110	11500	11880	12260	12640	13020	13400		

1) The above inflation pressures are minimum values. On front axle use it is recommended to use the table values increased with 1,0 bar, but not exceed 9,0 bar pressures.