

Nokian Truck Tyres

Tyre size	Pattern design	Load Index Speed Symbol	Additional marking	Fitting Single/ Dual	Speed symbol	Reference speed (km/h)	Maximum load capacity per axle (kg) at various cold inflation pressures (bar) 1)										
							6,50	6,75	7,00	7,25	7,50	7,75	8,00	8,25	8,50	8,75	9,00
295/80R22.5	NTR 32 NTR 45	152/148M 152/148M	- -	Single	M	130	5570	5760	5950	6150	6340	6530	6720	6910	<b>7100</b>		
				Dual	M	130	9890	10230	10570	10910	11240	11580	11920	12260	<b>12600</b>		
315/70R22.5	NTR 32 NTR 45	154/150L 154/150L	152/148M 152/148M	Single	L	120	5590	5780	5970	6160	6350	6540	6730	6930	7120	7310	<b>7500</b>
				Dual	L	120	9980	10320	10660	11010	11350	11690	12030	12370	12720	13060	<b>13400</b>
				Single	M	130	5570	5760	5950	6150	6340	6530	6720	6910	<b>7100</b>		
				Dual	M	130	9890	10230	10570	10910	11240	11580	11920	12260	<b>12600</b>		
315/80R22.5	NTR 32 NTR 45	154/150M 154/150M	156/150L 156/150L	Single	M	130	6050	6260	6460	6670	6880	7090	7290	<b>7500</b>			
				Dual	M	130	10810	11180	11550	11920	12290	12660	13030	<b>13400</b>			
				Single	L	120	6280	6490	6710	6920	7140	7350	7570	7780	<b>8000</b>		
				Dual	L	120	10810	11180	11550	11920	12290	12660	13030	<b>13400</b>			
315/80R22.5	NTR 68	156/150K	-	Single	K	110	6450	6670	6890	7120	7340	7560	7780	<b>8000</b>			
				Dual	K	110	10810	11180	11550	11920	12290	12660	13030	<b>13400</b>			
13R22.5	NTR 68	154/150K	156/150G	Single	K	110	6220	6430	6650	6860	7070	7290	<b>7500</b>				
				Dual	K	110	11110	11500	11880	12260	12640	13020	<b>13400</b>				
				Single	G	90	6280	6490	6710	6920	7140	7350	7570	7780	<b>8000</b>		
				Dual	G	90	11110	11500	11880	12260	12640	13020	<b>13400</b>				
385/65R22.5	NTR 72S	158L	160K	Single	L	120	6670	6900	7130	7360	7590	7810	8040	8270	<b>8500</b>		
				Single	K	110	6700	6930	7160	7390	7620	7850	8080	8310	8540	8770	<b>9000</b>

1) The above inflation pressures are minimum values. On front axle use it is recommended to use the table values increased with 1,0 bar, but not exceed 9,0 bar pressures.