

Nokian Tyres plc

Tyre Size	Pattern Design	Load Index, Speed Symbol	Additional Marking	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Revolutions per km	Revolutions per mile	Minimum Dual Spacing (mm)
275/70R22.5	NTR 32	148/145M	-	8.25 , 7.50	957	277	444	2939	340	548	311
295/80R22.5	NTR 32	152/148M	-	9.00 , 8.25	1040	298	482	3165	316	508	335
315/70R22.5	NTR 32	154/150L	152/148M	9.00 , 9.75	1015	310	470	3113	321	517	351
315/80R22.5	NTR 32	154/150M	156/150L	9.00 , 9.75	1072	310	495	3261	307	494	351
295/80R22.5	NTR 45	152/148M	-	9.00 , 8.25	1049	300	487	3169	316	508	335
315/70R22.5	NTR 45	154/150L	152/148M	9.00 , 9.75	1014	312	467	3075	325	523	351
315/80R22.5	NTR 45	154/150M	156/150L	9.00 , 9.75	1080	314	499	3256	307	494	351
315/80R22.5	NTR 68	156/150K	-	9.00 , 9.75	1081	312	498	3297	303	488	351
13R22.5	NTR 68	154/150K	156/150G	9.75 , 9.00	1124	328	524	3433	291	469	360
265/70R19.5	NTR 72	143/141J	-	7.50 , 6.75, 8.25	866	262	395	2636	379	611	295
385/55R22.5	NTR 72S	160K	158L	11.75 , 12.25	1001	381	464	3080	325	523	-
385/65R22.5	NTR 72S	158L	160K	11.75 , 12.25	1068	386	492	3277	305	491	-
385/65R22.5	NTR 73S	158L	160K	11.75 , 12.25	1069	388	494	3279	305	491	-