

Tyre size	Pattern design	Load Index Speed Symbol	Additional marking	Fitting Single/ Dual	Speed symbol	Reference speed (km/h)	Maximum load capacity per axle (kg) at various cold inflation pressures (bar) 1)										
							6,50	6,75	7,00	7,25	7,50	7,75	8,00	8,25	8,50	8,75	9,00
265/70R19.5	NTR-827 NTR-844	143/141J	-	Single	J	100	4280	4420	4570	4720	4860	5010	5160	5300	5450		
				Dual	J	100	8090	8360	8640	8920	9190	9470	9750	10020	10300		
275/70R22.5	NTR-844	148/145L	-	Single	L	120	4690	4850	5010	5170	5340	5500	5660	5820	5980	6140	6300
				Dual	L	120	8640	8940	9230	9530	9830	10120	10420	10710	11010	11310	11600
295/80R22.5	NTR-843 NTR-861 NTR-831 HKPL TRUCK E	152/148M 152/148M 152/148M 152/148M	- - - -	Single	M	130	5570	5760	5950	6150	6340	6530	6720	6910	7100		
				Dual	M	130	9890	10230	10570	10910	11240	11580	11920	12260	12600		
				Single	L	120	5590	5780	5970	6160	6350	6540	6730	6930	7120	7310	7500
				Dual	L	120	9980	10320	10660	11010	11350	11690	12030	12370	12720	13060	13400
315/70R22.5	NTR-843 NTR-831	152/148M 152/148M	154/150L 154/150L	Single	M	130	5570	5760	5950	6150	6340	6530	6720	6910	7100		
				Dual	M	130	9890	10230	10570	10910	11240	11580	11920	12260	12600		
				Single	L	120	5590	5780	5970	6160	6350	6540	6730	6930	7120	7310	7500
				Dual	L	120	9980	10320	10660	11010	11350	11690	12030	12370	12720	13060	13400
315/80R22.5	NTR-861 NTR-831 HKPL TRUCK E HKPL TRUCK F	154/150M 154/150M 154/150M 154/150M	156/150L 156/150L 156/150L 156/150L	Single	M	130	6050	6260	6460	6670	6880	7090	7290	7500			
				Dual	M	130	10810	11180	11550	11920	12290	12660	13030	13400			
				Single	L	120	6280	6490	6710	6920	7140	7350	7570	7780	8000		
				Dual	L	120	10810	11180	11550	11920	12290	12660	13030	13400			
385/65R22.5	NTR-844 HKPL TRUCK F	160K 160K	158L 158L	Single	K	110	6700	6930	7160	7390	7620	7850	8080	8310	8540	8770	9000
				Single	L	120	6670	6900	7130	7360	7590	7810	8040	8270	8500		

1) The above inflation pressures are minimum values. On front axle use it is recommended to use the table values increased with 1,0 bar, but not exceed 9,0 bar pressures.