

VF600/55R26.5 167D NOKIAN TYRES COUNTRY KING G2 SB TL

PRODUCT CODE	T445880
APPLICATION	Trailer
LI / SPEED SYMBOL	167D
RIM RECOMMENDED	AG20.00
TYPE APPROVAL	E4 106R-006652



LOAD CAPACITY FOR TRAILER, KG

Pressure (kPa)	Speed (km/h)												
	0	10	15	20	25	30	35	40	45	50	55	60	65
80	4690	3770	3635	3495	3360	3245	3105	2965	2830	2690	2555	2440	2300
120	5915	4755	4580	4410	4235	4090	3915	3740	3565	3395	3220	3075	2900
160	7240	5820	5610	5395	5185	5005	4795	4580	4365	4155	3940	3765	3550
200	8415	6765	6520	6270	6025	5815	5570	5320	5075	4825	4580	4375	4125
240	9690	7790	7505	7220	6935	6700	6415	6130	5845	5560	5275	5035	4750
280	11120	8940	8610	8285	7955	7685	7360	7030	6705	6375	6050	5775	5450

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1353 mm	1359 mm
TIRE WIDTH	620 mm	641 mm
PATTERN DEPTH	24 mm	
PATTERN DEPTH ON TIE BAR		
MAX. INFLATION PRESSURE	400 kPa	

STATIC LOADED RADIUS 596 mm @ 5450 kg / 280 kPa

DYNAMIC ROLLING CIRCUMFERENCE 4104 mm @ 5450 kg / 280 kPa

DYNAMIC ROLLING RADIUS 653 mm @ 5450 kg / 280 kPa

SPEED RADIUS INDEX 625

TUBELESS VALVE TR618A

BELT MATERIAL Steel

VOLUME 515 l 100%
386 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
515	136	386	102	317	84	162	356	479	1056

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the

ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/