

# 265/70R19.5 143/141J NOKIAN TYRES R-TRUCK TRAILER

## Reliability for on/off-road use

PRODUCT CODE	T675295
APPLICATION	Trailer
LI / SPEED SYMBOL	143/141J
RIM RECOMMENDED	7.50
RIM PERMITTED	6.75, 8.25
TYPE APPROVAL	E4 0054011, E4 0414424 S2W2R3B



## LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	100	4200	4330	4460	4580	4710	4840	4960	5080	5210	5330	5450
Dual	100	7940	8180	8420	8660	8900	9140	9370	9610	9840	10070	10300

## TIRE DIMENSIONS

OVERALL DIAMETER	872 mm
TIRE WIDTH	259 mm
STATIC LOADED RADIUS	403 mm
ROLLING CIRCUMFERENCE	2601 mm
MIN. DUAL SPACING	295 mm
PATTERN DEPTH	15 mm

## EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	A
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)