

## 315/70R22.5 154/150L NOKIAN TYRES E-TRUCK DRIVE

Reliable all-season tyres for medium and regional haul transport.

PRODUCT CODE	T675296
APPLICATION	Drive
LI / SPEED SYMBOL	154/150L
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0054834, E4 0414988 S2W2R3B



### LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	75	12745	13140	13515	13910	14285	14660	15060	15430	15785	16160	16535
Dual	75	22775	23480	24165	24845	25530	26215	26895	27560	28220	28880	29540

### TIRE DIMENSIONS

OVERALL DIAMETER	40.2 in
TIRE WIDTH	12.1 in
STATIC LOADED RADIUS	18.7 in
ROLLING CIRCUMFERENCE	122.7 in
MIN. DUAL SPACING	13.8 in
PATTERN DEPTH	25/32 in

### EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	74 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)