

315/70R22.5 156/150L NOKIAN TYRES E-TRUCK STEER

Steady handling in the long run

PRODUCT CODE	T675297
APPLICATION	Steer
LI / SPEED SYMBOL	156/150L
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0054833, E4 0414987 S2W2R3B



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	75	13605	14020	14420	14835	15235	15655	16050	16445	16845	17240	17635
Dual	75	22775	23480	24165	24845	25530	26215	26895	27560	28220	28880	29540

TIRE DIMENSIONS

OVERALL DIAMETER	40 in
TIRE WIDTH	12.2 in
STATIC LOADED RADIUS	18.5 in
ROLLING CIRCUMFERENCE	121.9 in
MIN. DUAL SPACING	13.8 in
PATTERN DEPTH	20/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/