

# 315/80R22.5 156/150L NOKIAN TYRES HAKKAPELIITTA TRUCK E2

Superior traction and optimized performance on severe winter conditions

PRODUCT CODE	T675289
APPLICATION	Drive
LI / SPEED SYMBOL	156/150L (154/150M)
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0054013, E4 0414426 S2W2R3B



## LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)								
		94	98	102	105	109	112	116	120	123
Single	75	14220	14660	15100	15520	15960	16380	16800	17220	17635
Dual	75	23830	24560	25285	26015	26720	27450	28155	28835	29540

## TIRE DIMENSIONS

OVERALL DIAMETER	43.1 in
TIRE WIDTH	12.3 in
STATIC LOADED RADIUS	19.8 in
ROLLING CIRCUMFERENCE	129.2 in
MIN. DUAL SPACING	13.8 in
PATTERN DEPTH	25/32 in

## EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	A
NOISE	73 dB
NOISE WAVES	A
STUDDABLE	Marked stud positions on tread Number of studs 174 pcs Recommended stud 11-15
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)