

710/45-26.5 24 173A8/180A2 NOKIAN TYRES FOREST KING F2 SF TT

Track grip for demanding forestry use

| | |
|--------------------------|-------------------------|
| PRODUCT CODE | T445589 |
| TIRE CLASSIFICATION CODE | LS-2 |
| APPLICATION | Forwarder and Harvester |
| LI / SPEED SYMBOL | 173A8 (180A2) |
| PLY RATING | 24 |
| RIM RECOMMENDED | AG24.00 |
| TYPE APPROVAL | E8 106R-000273 |



LOAD CAPACITY FOR FORWARDER AND HARVESTER, KG

Forestry service (LT)

| Pressure (kPa) | Speed (km/h) |
|----------------|--------------|
| | 10 |
| 160 | 3550 |
| 200 | 3875 |
| 240 | 4250 |
| 280 | 4750 |
| 320 | 5000 |
| 360 | 5600 |
| 400 | 6000 |
| 450 | 6500 |
| 500 | 6900 |
| 600 | 8000 |

Road

| Pressure (kPa) | Speed (km/h) | | |
|----------------|--------------|------|------|
| | 20 | 30 | 40 |
| 160 | 3565 | 3105 | 2900 |
| 200 | 3875 | 3370 | 3150 |
| 240 | 4245 | 3690 | 3450 |
| 280 | 4765 | 4145 | 3875 |
| 320 | 5075 | 4415 | 4125 |
| 360 | 5535 | 4815 | 4500 |
| 400 | 5995 | 5215 | 4875 |
| 450 | 6520 | 5670 | 5300 |
| 500 | 6890 | 5990 | 5600 |
| 600 | 7995 | 6955 | 6500 |

TIRE DIMENSIONS

| | New tire | Max. in service |
|-------------------------|----------|-----------------|
| OVERALL DIAMETER | 1345 mm | 1357 mm |
| TIRE WIDTH | 708 mm | 785 mm |
| PATTERN DEPTH | 35 mm | |
| MAX. INFLATION PRESSURE | 600 kPa | |

| | |
|-------------------------------|-----------------------------|
| STATIC LOADED RADIUS | 621 mm @ 8000 kg / 600 kPa |
| DYNAMIC ROLLING CIRCUMFERENCE | 4084 mm @ 8000 kg / 600 kPa |
| DYNAMIC ROLLING RADIUS | 650 mm @ 8000 kg / 600 kPa |
| TUBE PRODUCT CODE | T55099 |
| TUBE VALVE | TR218A |
| BREAKER MATERIAL | Steel |
| VOLUME | 500 l 100% 375 l 75% |

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% | | Water filling 75% | | Water/salt filling (75% / -30°C) | | | | Total weight increase | |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|------|
| | | | | Water | | Salt | | | |
| Litres | Gallons | Litres | Gallons | Litres | Gallons | kg | lbs | kg | lbs |
| 500 | 132 | 375 | 99 | 308 | 81 | 157 | 346 | 465 | 1025 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/