

650/60-26.5 20 172A8/179A2 NOKIAN TYRES FOREST KING TRS L-2 SF TT

Reliable grip and traction

PRODUCT CODE	T445395
TIRE CLASSIFICATION CODE	L-2
APPLICATION	Forwarder and Harvester
LI / SPEED SYMBOL	172A8 (179A2)
PLY RATING	20
RIM RECOMMENDED	AG20.00
TYPE APPROVAL	E8 106R-000275



LOAD CAPACITY FOR FORWARDER AND HARVESTER, LB

Forestry service (LT)

Pressure (psi)	Speed (mph)
	5
23	8820
29	9920
35	10470
41	12015
46	12345
52	13560
58	15210
65	16095
73	17085

Road

Pressure (psi)	Speed (mph)		
	12	17.5	25
23	8820	7670	7165
29	9900	8610	8045
35	10505	9140	8545
41	11860	10320	9645
46	12545	10915	10195
52	13560	11795	11025
58	15190	13205	12345
65	16270	14155	13230
73	17085	14860	13890

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	58.2 in	59.3 in
TIRE WIDTH	25.8 in	27.4 in
PATTERN DEPTH	63/32 in	
PATTERN DEPTH ON TIE BAR	53/32 in	
MAX. INFLATION PRESSURE	80 psi	

STATIC LOADED RADIUS	26.6 in @ 17100 lb / 73 psi
DYNAMIC ROLLING CIRCUMFERENCE	175.9 in @ 17100 lb / 73 psi
DYNAMIC ROLLING RADIUS	28 in @ 17100 lb / 73 psi
TUBE PRODUCT CODE	T55102
TUBE VALVE	TR218A
BREAKER MATERIAL	Steel
VOLUME	145 gallons 100% 109 gallons 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
550	145	413	109	338	89	173	380	511	1127

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/