

# 28L-26 26 173A6/185A2 NOKIAN TYRES FOREST KING TRS LS-2 SF TL

A traction tire with excellent grip for demanding conditions

|                          |                            |
|--------------------------|----------------------------|
| PRODUCT CODE             | T445516                    |
| TIRE CLASSIFICATION CODE | LS-2                       |
| APPLICATION              | Skidder and Feller buncher |
| LI / SPEED SYMBOL        | 173A6 (185A2)              |
| PLY RATING               | 26                         |
| RIM RECOMMENDED          | DW25B                      |
| TYPE APPROVAL            | E8 106R-000297             |



## LOAD CAPACITY FOR SKIDDER AND FELLER BUNCHER, KG

### Log Skidder Drive Wheel for Cable and Grapple Skidders Forestry Service

| Pressure (kPa) | Speed (km/h) |
|----------------|--------------|
|                | 10           |
| 170            | 5300         |
| 210            | 6000         |
| 240            | 6700         |
| 280            | 7300         |
| 380            | 9200         |

### Log Skidder Drive wheel (other than on Cable or Grapple skidder) Transport Service

| Pressure (kPa) | Speed (km/h) |      |      |      |
|----------------|--------------|------|------|------|
|                | 15           | 25   | 30   | 40   |
| 140            | 4500         | 4150 | 3750 | 3400 |
| 170            | 5100         | 4700 | 4250 | 3850 |
| 210            | 5700         | 5250 | 4750 | 4300 |
| 240            | 6200         | 5650 | 5150 | 4650 |
| 340            | 7800         | 7150 | 6500 | 5850 |

**TIRE DIMENSIONS**

|                          | New tire | Max. in service |
|--------------------------|----------|-----------------|
| OVERALL DIAMETER         | 1641 mm  | 1703 mm         |
| TIRE WIDTH               | 741 mm   | 771 mm          |
| PATTERN DEPTH            | 53 mm    |                 |
| PATTERN DEPTH ON TIE BAR | 49 mm    |                 |
| MAX. INFLATION PRESSURE  | 400 kPa  |                 |

|                               |                             |
|-------------------------------|-----------------------------|
| STATIC LOADED RADIUS          | 748 mm @ 6500 kg / 340 kPa  |
| STATIC LOADED RADIUS          | 733 mm @ 9250 kg / 400 kPa  |
| DYNAMIC ROLLING CIRCUMFERENCE | 4945 mm @ 6500 kg / 340 kPa |
| DYNAMIC ROLLING CIRCUMFERENCE | 4945 mm @ 9250 kg / 400 kPa |
| DYNAMIC ROLLING RADIUS        | 787 mm @ 6500 kg / 340 kPa  |
| DYNAMIC ROLLING RADIUS        | 787 mm @ 9250 kg / 400 kPa  |
| TUBE PRODUCT CODE             | T55101                      |
| TUBE VALVE                    | TR218A                      |
| TUBELESS VALVE                | TR618A                      |
| BREAKER MATERIAL              | Steel                       |
| VOLUME                        | 800 l 100%<br>600 l 75%     |

**WATER AND SALT BALLASTING**

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% |         | Water filling 75% |         | Water/salt filling (75% / -30°C) |         |      |     | Total weight increase |      |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|------|
|                  |         |                   |         | Water                            |         | Salt |     |                       |      |
| Litres           | Gallons | Litres            | Gallons | Litres                           | Gallons | kg   | lbs | kg                    | lbs  |
| 800              | 211     | 600               | 159     | 492                              | 130     | 251  | 553 | 743                   | 1638 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)