

600/50-22.5 24 173A8 NOKIAN TYRES EXCAVATOR SF TL

Excavator tire for soft surfaces

| | |
|-------------------|-------------------|
| PRODUCT CODE | T445604 |
| APPLICATION | Wheeled excavator |
| LI / SPEED SYMBOL | 173A8 |
| PLY RATING | 24 |
| RIM RECOMMENDED | AG20.00 |
| TYPE APPROVAL | E8 106R-001601 |



LOAD CAPACITY FOR WHEELED EXCAVATOR, LB

Constant load

| Pressure (psi) | Speed (mph) | | | | | | | | | | |
|----------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | 0 | 2.5 | 5 | 10 | 12 | 15 | 17.5 | 22.5 | 25 | 27.5 | 30 |
| 29 | 12675 | 7990 | 6890 | 6230 | 6010 | 5840 | 5730 | 5620 | 5510 | 5290 | 5015 |
| 35 | 15210 | 9590 | 8265 | 7475 | 7210 | 7010 | 6880 | 6745 | 6615 | 6350 | 6020 |
| 46 | 19015 | 11995 | 10340 | 9350 | 9015 | 8765 | 8600 | 8435 | 8265 | 7935 | 7530 |
| 52 | 21550 | 13590 | 11720 | 10595 | 10220 | 9930 | 9745 | 9555 | 9370 | 8995 | 8530 |
| 58 | 23455 | 14780 | 12745 | 11520 | 11110 | 10815 | 10605 | 10405 | 10195 | 9790 | 9280 |
| 65 | 26115 | 16470 | 14200 | 12830 | 12380 | 12035 | 11805 | 11585 | 11355 | 10900 | 10330 |
| 73 | 28395 | 17900 | 15430 | 13955 | 13460 | 13085 | 12840 | 12590 | 12345 | 11850 | 11235 |
| 80 | 31185 | 19665 | 16955 | 15320 | 14780 | 14375 | 14100 | 13835 | 13560 | 13020 | 12335 |
| 87 | 32960 | 20780 | 17915 | 16195 | 15620 | 15190 | 14905 | 14615 | 14330 | 13755 | 13040 |

TIRE DIMENSIONS

| | New tire | Max. in service |
|-------------------------|----------|-----------------|
| OVERALL DIAMETER | 45.2 in | 47.8 in |
| TIRE WIDTH | 23 in | 25.1 in |
| PATTERN DEPTH | 50/32 in | |
| MAX. INFLATION PRESSURE | 87 psi | |

STATIC LOADED RADIUS 20.4 in @ 14300 lb / 87 psi

DYNAMIC ROLLING CIRCUMFERENCE 139 in @ 14300 lb / 87 psi

DYNAMIC ROLLING RADIUS 22.1 in @ 14300 lb / 87 psi

SPEED RADIUS INDEX 550

TUBE PRODUCT CODE T55089

TUBE VALVE TR218A

TUBELESS VALVE TR618A

BREAKER MATERIAL Steel

VOLUME 71 gallons 100%
53 gallons 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% | | Water filling 75% | | Water/salt filling (75% / -30°C) | | | | Total weight increase | |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|-----|
| | | | | Water | | Salt | | | |
| Litres | Gallons | Litres | Gallons | Litres | Gallons | kg | lbs | kg | lbs |
| 270 | 71 | 203 | 53 | 166 | 44 | 85 | 187 | 251 | 553 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/