

# 600/50-22.5 24 173A8 NOKIAN TYRES EXCAVATOR SF TL

Excavator tire for soft surfaces

<b>PRODUCT CODE</b>	T445604
<b>APPLICATION</b>	Wheeled excavator
<b>LI / SPEED SYMBOL</b>	173A8
<b>PLY RATING</b>	24
<b>RIM RECOMMENDED</b>	AG20.00 Always make sure that rim is suitable for intended use. Please see Nokian Tyres rim recommendations.
<b>TYPE APPROVAL</b>	E8 106R-001601



## LOAD CAPACITY FOR WHEELED EXCAVATOR, LB

### Constant load

Pressure (psi)	Speed (mph)										
	0	2.5	5	10	12	15	17.5	22.5	25	27.5	30
29	12675	7990	6890	6230	6010	5840	5730	5620	5510	5290	5015
35	15210	9590	8265	7475	7210	7010	6880	6745	6615	6350	6020
46	19015	11995	10340	9350	9015	8765	8600	8435	8265	7935	7530
52	21550	13590	11720	10595	10220	9930	9745	9555	9370	8995	8530
58	23455	14780	12745	11520	11110	10815	10605	10405	10195	9790	9280
65	26115	16470	14200	12830	12380	12035	11805	11585	11355	10900	10330
73	28395	17900	15430	13955	13460	13085	12840	12590	12345	11850	11235
80	31185	19665	16955	15320	14780	14375	14100	13835	13560	13020	12335
87	32960	20780	17915	16195	15620	15190	14905	14615	14330	13755	13040

**TIRE DIMENSIONS**

	New tire	Max. in service
OVERALL DIAMETER	45.2 in	47.8 in
TIRE WIDTH	23 in	25.1 in
PATTERN DEPTH	50/32 in	
PATTERN DEPTH ON TIE BAR		
MAX. INFLATION PRESSURE	87 psi	

STATIC LOADED RADIUS	20.4 in @ 14300 lb / 87 psi
DYNAMIC ROLLING CIRCUMFERENCE	139 in @ 14300 lb / 87 psi
DYNAMIC ROLLING RADIUS	22.1 in @ 14300 lb / 87 psi
SPEED RADIUS INDEX	550
TUBE PRODUCT CODE	T55089
TUBE VALVE	TR218A
TUBELESS VALVE	TR618A
BREAKER MATERIAL	Steel
VOLUME	71 gallons 100% 53 gallons 75%

**WATER AND SALT BALLASTING**

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
270	71	203	53	166	44	85	187	251	553

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)