

650/45-22.5 24 175A8 NOKIAN TYRES GROUND KARE SF TL

Excavator and backhoe loader tire for versatile contracting work

| | |
|--------------------------|---|
| PRODUCT CODE | T445664 |
| APPLICATION | Wheeled excavator |
| LI / SPEED SYMBOL | 175A8 |
| PLY RATING | 24 |
| RIM RECOMMENDED | AG22.00 Always make sure that rim is suitable for intended use. Please see Nokian Tyres rim recommendations. |
| RIM PERMITTED | AG20.00 |
| TYPE APPROVAL | E8 106R-001143 |



LOAD CAPACITY FOR WHEELED EXCAVATOR, LB

Constant load

| Pressure (psi) | Speed (mph) | | | | | | | | | | |
|----------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | 0 | 2.5 | 5 | 10 | 12 | 15 | 17.5 | 22.5 | 25 | 27.5 | 30 |
| 52 | 22190 | 13990 | 12060 | 10900 | 10515 | 10230 | 10030 | 9845 | 9645 | 9260 | 8775 |
| 58 | 24085 | 15190 | 13095 | 11840 | 11420 | 11100 | 10890 | 10680 | 10470 | 10055 | 9535 |
| 65 | 26875 | 16945 | 14605 | 13205 | 12730 | 12390 | 12145 | 11915 | 11685 | 11220 | 10635 |
| 73 | 29410 | 18540 | 15985 | 14450 | 13935 | 13560 | 13295 | 13040 | 12785 | 12280 | 11640 |
| 80 | 31945 | 20140 | 17360 | 15695 | 15135 | 14725 | 14440 | 14165 | 13890 | 13340 | 12645 |
| 87 | 34985 | 22055 | 19015 | 17185 | 16580 | 16125 | 15820 | 15520 | 15210 | 14605 | 13845 |

TIRE DIMENSIONS

| | New tire | Max. in service |
|--------------------------|----------|-----------------|
| OVERALL DIAMETER | 45.1 in | 47.2 in |
| TIRE WIDTH | 26.1 in | 27.4 in |
| PATTERN DEPTH | 33/32 in | |
| PATTERN DEPTH ON TIE BAR | | |
| MAX. INFLATION PRESSURE | 87 psi | |

| | |
|-------------------------------|-----------------------------------|
| STATIC LOADED RADIUS | 20.6 in @ 15200 lb / 87 psi |
| DYNAMIC ROLLING CIRCUMFERENCE | 137.5 in @ 15200 lb / 87 psi |
| DYNAMIC ROLLING RADIUS | 21.9 in @ 15200 lb / 87 psi |
| SPEED RADIUS INDEX | 550 |
| TUBE PRODUCT CODE | T55092 |
| TUBE VALVE | TR218A |
| TUBELESS VALVE | TR618A |
| BREAKER MATERIAL | Steel |
| STUDDABLE | Yes |
| VOLUME | 79 gallons 100% 59 gallons 75% |

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% | | Water filling 75% | | Water/salt filling (75% / -30°C) | | | | Total weight increase | |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|-----|
| | | | | Water | | Salt | | | |
| Litres | Gallons | Litres | Gallons | Litres | Gallons | kg | lbs | kg | lbs |
| 300 | 79 | 225 | 59 | 185 | 49 | 94 | 207 | 279 | 615 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/