

## 600/50R22.5 163D NOKIAN TYRES CT SB TL

### Stability for transporting high loads

PRODUCT CODE	T445627
APPLICATION	Trailer
LI / SPEED SYMBOL	163D
RIM RECOMMENDED	AG20.00
TYPE APPROVAL	E8 106R-001195



### LOAD CAPACITY FOR TRAILER, LB

#### Mixed

Pressure (psi)	Speed (mph)											
	5	10	12	15	17.5	22.5	25	27.5	30	35	37.5	40
12	5755	5535	5280	5050	4830	4610	4345	4125	3870	3650	3415	3195
17	7340	7055	6735	6450	6160	5875	5545	5260	4940	4650	4365	4080
23	8885	8545	8145	7805	7450	7110	6715	6370	5975	5635	5280	4940
29	9920	9535	9095	8710	8320	7935	7495	7110	6670	6285	5895	5510
35	11510	11055	10550	10095	9655	9205	8695	8245	7740	7285	6845	6395
41	12895	12400	11830	11320	10825	10320	9745	9250	8675	8170	7670	7165
46	14485	13920	13285	12710	12145	11585	10945	10385	9735	9170	8610	8045
52	15875	15255	14550	13935	13315	12700	11995	11375	10670	10055	9435	8820
58	17360	16690	15915	15245	14560	13890	13120	12445	11675	11000	10320	9645
65	18355	17635	16820	16115	15400	14685	13865	13150	12335	11630	10915	10195
73	19345	18595	17735	16985	16225	15475	14615	13865	13005	12260	11495	10750

**TIRE DIMENSIONS**

	New tire	Max. in service
OVERALL DIAMETER	46.2 in	47.1 in
TIRE WIDTH	23.5 in	24.4 in
PATTERN DEPTH	28/32 in	
MAX. INFLATION PRESSURE	73 psi	

STATIC LOADED RADIUS	20.8 in @ 10700 lb / 73 psi
DYNAMIC ROLLING CIRCUMFERENCE	140.7 in @ 10700 lb / 73 psi
DYNAMIC ROLLING RADIUS	22.4 in @ 10700 lb / 73 psi
SPEED RADIUS INDEX	550
TUBE PRODUCT CODE	T55089
TUBE VALVE	TR218A
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
VOLUME	98 gallons 100% 74 gallons 75%

**WATER AND SALT BALLASTING**

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
370	98	278	73	228	60	116	256	344	758

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)