650/65R26.5 174D NOKIAN TYRES ELS SB TL

Reduced ground pressure for soil protection

PRODUCT CODE	T445465
APPLICATION	Trailer / Tractor
LI / SPEED SYMBOL	174D
RIM RECOMMENDED	AG20.00
TYPE APPROVAL	E8 106R-001188

LOAD CAPACITY FOR TRAILER, LB

Mixed

Pressure (psi)	**Speed** (mph)											
	5	**10**	**12**	**15**	**17.5**	**22.5**	**25**	**27.5**	**30**	**35**	**37.5**	**40**
12	8655	8310	7925	7595	7255	6925	6535	6195	5820	5480	5150	4805
17	11110	10680	10185	9755	9325	8885	8400	7960	7475	7035	6605	6175
23	13295	12775	12190	11675	11155	10635	10040	9525	8940	8420	7905	7385
29	15375	14780	14100	13505	12895	12300	11620	11025	10340	9745	9140	8545
35	17855	17165	16370	15675	14980	14285	13490	12800	12005	11310	10615	9920
41	20435	19645	18740	17935	17140	16345	15445	14650	13735	12940	12145	11355
46	22225	21365	20370	19510	18640	17780	16790	15930	14935	14075	13205	12345
52	24405	23455	22375	21420	20470	19520	18440	17495	16400	15455	14505	13560
58	26590	25550	24370	23335	22300	21275	20085	19060	17870	16845	15805	14770

TIRE DIMENSIONS

	New tire	**Max. in service**
OVERALL DIAMETER	59.6 in	61.1 in
TIRE WIDTH	25.4 in	26.7 in
PATTERN DEPTH	30/32 in	
PATTERN DEPTH ON TIE BAR		
MAX. INFLATION PRESSURE	58 psi	

STATIC LOADED RADIUS	26.8 in @ 14800 lb / 58 psi
DYNAMIC ROLLING CIRCUMFERENCE	181.8 in @ 14800 lb / 58 psi
DYNAMIC ROLLING RADIUS	28.9 in @ 14800 lb / 58 psi
SPEED RADIUS INDEX	725
TUBE PRODUCT CODE	T55897
TUBE VALVE	TR218A
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
VOLUME	192 gallons 100% 144 gallons 75%

Nokian Raskaat Renkaat Oy
Nokian Heavy Tyres Ltd
Pirkkalaistie 7, P.O. Box 20
FI-37101 Nokia, Finland
Puh. 010 401 7000
Tel. +358 10 401 7000
Business ID 2001415 Nokia
VAT number FI20014151
www.nokiantyres.com/heavy

WATER AND SALT BALLASTING

(CaCl2, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
725	192	544	144	446	118	227	501	673	1484

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:
- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: **www.nokiantyres.com/heavy/technical-tire-manual/**