

600/50R22.5 159D NOKIAN TYRES COUNTRY KING SB TL

Sturdy and versatile flotation tire

PRODUCT CODE	T445441
APPLICATION	Trailer
LI / SPEED SYMBOL	159D
RIM RECOMMENDED	AG20.00
TYPE APPROVAL	E8 106R-001504



LOAD CAPACITY FOR TRAILER, KG

Mixed

Pressure (kPa)	Speed (km/h)											
	10	15	20	25	30	35	40	45	50	55	60	65
80	2610	2510	2395	2290	2190	2090	1970	1870	1755	1655	1550	1450
120	3330	3200	3055	2925	2795	2665	2515	2385	2240	2110	1980	1850
160	4030	3875	3695	3540	3380	3225	3045	2890	2710	2555	2395	2240
200	4500	4325	4125	3950	3775	3600	3400	3225	3025	2850	2675	2500
240	5220	5015	4785	4580	4380	4175	3945	3740	3510	3305	3105	2900
280	5850	5625	5365	5135	4910	4680	4420	4195	3935	3705	3480	3250
320	6570	6315	6025	5765	5510	5255	4965	4710	4415	4160	3905	3650
360	7200	6920	6600	6320	6040	5760	5440	5160	4840	4560	4280	4000
400	7875	7570	7220	6915	6605	6300	5950	5645	5295	4990	4680	4375

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1170 mm	1196 mm
TIRE WIDTH	594 mm	621 mm
PATTERN DEPTH	18 mm	
MAX. INFLATION PRESSURE	400 kPa	

STATIC LOADED RADIUS	533 mm @ 4375 kg / 400 kPa
DYNAMIC ROLLING CIRCUMFERENCE	3575 mm @ 4375 kg / 400 kPa
DYNAMIC ROLLING RADIUS	569 mm @ 4375 kg / 400 kPa
SPEED RADIUS INDEX	550
TUBE PRODUCT CODE	T55089
TUBE VALVE	TR218A
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
VOLUME	370 l 100% 278 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
370	98	278	73	228	60	116	256	344	758

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/