

# 620/60R26.5 169D NOKIAN TYRES COUNTRY KING SB TL

Sturdy and versatile flotation tire

PRODUCT CODE	T445404
APPLICATION	Trailer
LI / SPEED SYMBOL	169D
RIM RECOMMENDED	AG20.00
TYPE APPROVAL	E8 106R-001500



## LOAD CAPACITY FOR TRAILER, KG

### Mixed

Pressure (kPa)	Speed (km/h)											
	10	15	20	25	30	35	40	45	50	55	60	65
80	3330	3200	3055	2925	2795	2665	2515	2385	2240	2110	1980	1850
120	4250	4085	3895	3730	3565	3400	3210	3045	2855	2690	2525	2360
160	5220	5015	4785	4580	4380	4175	3945	3740	3510	3305	3105	2900
200	6030	5795	5530	5295	5060	4825	4555	4320	4055	3820	3585	3350
240	6975	6705	6395	6125	5850	5580	5270	5000	4690	4420	4145	3875
280	7875	7570	7220	6915	6605	6300	5950	5645	5295	4990	4680	4375
320	8775	8435	8045	7705	7360	7020	6630	6290	5900	5560	5215	4875
360	9540	9170	8745	8375	8005	7630	7210	6835	6415	6040	5670	5300
400	10440	10035	9570	9165	8760	8350	7890	7480	7020	6610	6205	5800

## TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1403 mm	1447 mm
TIRE WIDTH	632 mm	656 mm
PATTERN DEPTH	20 mm	
PATTERN DEPTH ON TIE BAR	17 mm	
MAX. INFLATION PRESSURE	400 kPa	

STATIC LOADED RADIUS 639 mm @ 5800 kg / 400 kPa

DYNAMIC ROLLING CIRCUMFERENCE 4291 mm @ 5800 kg / 400 kPa

DYNAMIC ROLLING RADIUS 683 mm @ 5800 kg / 400 kPa

SPEED RADIUS INDEX 675

TUBE PRODUCT CODE T55098

TUBE VALVE TR218A

TUBELESS VALVE TR618A

BELT MATERIAL Steel

VOLUME 555 l 100%  
416 l 75%

**WATER AND SALT BALLASTING**

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
555	147	416	110	342	90	174	384	516	1138

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)