

# 650/65R26.5 174D NOKIAN TYRES COUNTRY KING SB TL

Sturdy and versatile flotation tire

|                   |                |
|-------------------|----------------|
| PRODUCT CODE      | T445440        |
| APPLICATION       | Trailer        |
| LI / SPEED SYMBOL | 174D           |
| RIM RECOMMENDED   | AG20.00        |
| TYPE APPROVAL     | E8 106R-000267 |



## LOAD CAPACITY FOR TRAILER, KG

### Mixed

| Pressure (kPa) | Speed (km/h) |       |       |       |       |      |      |      |      |      |      |      |
|----------------|--------------|-------|-------|-------|-------|------|------|------|------|------|------|------|
|                | 10           | 15    | 20    | 25    | 30    | 35   | 40   | 45   | 50   | 55   | 60   | 65   |
| 80             | 3925         | 3770  | 3595  | 3445  | 3290  | 3140 | 2965 | 2810 | 2640 | 2485 | 2335 | 2180 |
| 120            | 5040         | 4845  | 4620  | 4425  | 4230  | 4030 | 3810 | 3610 | 3390 | 3190 | 2995 | 2800 |
| 160            | 6030         | 5795  | 5530  | 5295  | 5060  | 4825 | 4555 | 4320 | 4055 | 3820 | 3585 | 3350 |
| 200            | 6975         | 6705  | 6395  | 6125  | 5850  | 5580 | 5270 | 5000 | 4690 | 4420 | 4145 | 3875 |
| 240            | 8100         | 7785  | 7425  | 7110  | 6795  | 6480 | 6120 | 5805 | 5445 | 5130 | 4815 | 4500 |
| 280            | 9270         | 8910  | 8500  | 8135  | 7775  | 7415 | 7005 | 6645 | 6230 | 5870 | 5510 | 5150 |
| 320            | 10080        | 9690  | 9240  | 8850  | 8455  | 8065 | 7615 | 7225 | 6775 | 6385 | 5990 | 5600 |
| 360            | 11070        | 10640 | 10150 | 9715  | 9285  | 8855 | 8365 | 7935 | 7440 | 7010 | 6580 | 6150 |
| 400            | 12060        | 11590 | 11055 | 10585 | 10115 | 9650 | 9110 | 8645 | 8105 | 7640 | 7170 | 6700 |

## TIRE DIMENSIONS

|                          | New tire | Max. in service |
|--------------------------|----------|-----------------|
| OVERALL DIAMETER         | 1519 mm  | 1553 mm         |
| TIRE WIDTH               | 656 mm   | 677 mm          |
| PATTERN DEPTH            | 20 mm    |                 |
| PATTERN DEPTH ON TIE BAR | 16 mm    |                 |
| MAX. INFLATION PRESSURE  | 400 kPa  |                 |

STATIC LOADED RADIUS 689 mm @ 6700 kg / 400 kPa

DYNAMIC ROLLING CIRCUMFERENCE 4656 mm @ 6700 kg / 400 kPa

DYNAMIC ROLLING RADIUS 741 mm @ 6700 kg / 400 kPa

SPEED RADIUS INDEX 725

TUBE PRODUCT CODE T55102

TUBE VALVE TR218A

TUBELESS VALVE TR618A

BELT MATERIAL Steel

VOLUME 723 l 100%  
542 l 75%

**WATER AND SALT BALLASTING**

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% |         | Water filling 75% |         | Water/salt filling (75% / -30°C) |         |      |     | Total weight increase |      |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|------|
|                  |         |                   |         | Water                            |         | Salt |     |                       |      |
| Litres           | Gallons | Litres            | Gallons | Litres                           | Gallons | kg   | lbs | kg                    | lbs  |
| 723              | 191     | 542               | 143     | 445                              | 118     | 227  | 500 | 672                   | 1482 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)