710/50R26.5 170D NOKIAN TYRES COUNTRY KING SB TL

Sturdy and versatile flotation tire

PRODUCT CODE	T445406
APPLICATION	Trailer
LI / SPEED SYMBOL	170D
RIM RECOMMENDED	AG24.00
TYPE APPROVAL	E8 106R-001502

LOAD CAPACITY FOR TRAILER, KG

Mixed

Pressure (kPa)	Speed (km/h)											
	10	**15**	**20**	**25**	**30**	**35**	**40**	**45**	**50**	**55**	**60**	**65**
80	3510	3375	3220	3080	2945	2810	2650	2515	2360	2225	2085	1950
120	4500	4325	4125	3950	3775	3600	3400	3225	3025	2850	2675	2500
160	5535	5320	5075	4860	4645	4430	4180	3965	3720	3505	3290	3075
200	6390	6140	5860	5610	5360	5110	4830	4580	4295	4045	3800	3550
240	7200	6920	6600	6320	6040	5760	5440	5160	4840	4560	4280	4000
280	8325	8000	7630	7310	6985	6660	6290	5965	5595	5275	4950	4625
320	9000	8650	8250	7900	7550	7200	6800	6450	6050	5700	5350	5000
360	10080	9690	9240	8850	8455	8065	7615	7225	6775	6385	5990	5600
400	11070	10640	10150	9715	9285	8855	8365	7935	7440	7010	6580	6150

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1405 mm	1411 mm
TIRE WIDTH	740 mm	741 mm
PATTERN DEPTH	21 mm	
PATTERN DEPTH ON TIE BAR	16 mm	
MAX. INFLATION PRESSURE	400 kPa	

STATIC LOADED RADIUS	646 mm @ 6000 kg / 400 kPa
DYNAMIC ROLLING CIRCUMFERENCE	4304 mm @ 6000 kg / 400 kPa
DYNAMIC ROLLING RADIUS	685 mm @ 6000 kg / 400 kPa
SPEED RADIUS INDEX	650
TUBE PRODUCT CODE	T55102
TUBE VALVE	TR218A
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
VOLUME	655 l 100% 491 l 75%

WATER AND SALT BALLASTING

(CaCl2, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
655	173	491	130	403	106	205	453	608	1340

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:
- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: **www.nokiantyres.com/heavy/technical-tire-manual/**