

## 650/65R38 175A8/170D NOKIAN TYRES TRI 2 SB TL

Reliable performance all year round

|                          |                |
|--------------------------|----------------|
| PRODUCT CODE             | T445443        |
| TIRE CLASSIFICATION CODE | R-4            |
| APPLICATION              | Tractor        |
| LI / SPEED SYMBOL        | 175A8 (170D)   |
| RIM RECOMMENDED          | DW20B          |
| RIM PERMITTED            | DW18L, DW23B   |
| TYPE APPROVAL            | E8 106R-001635 |



### LOAD CAPACITY FOR TRACTOR, KG

#### Constant load

| Pressure<br>(kPa) | Speed (km/h) |       |          |      |      |      |             |      |      |      |      |      |      |      |
|-------------------|--------------|-------|----------|------|------|------|-------------|------|------|------|------|------|------|------|
|                   | 0            | 5     | 10<br>LT | 15   | 20   | 25   | 30<br>10 HT | 35   | 40   | 45   | 50   | 55   | 60   | 65   |
| 80                | 6995         | 4425  | 3815     | 3445 | 3340 | 3235 | 3180        | 3125 | 3050 | 2970 | 2860 | 2785 | 2730 | 2650 |
| 120               | 9110         | 5760  | 4970     | 4485 | 4345 | 4210 | 4140        | 4070 | 3970 | 3865 | 3725 | 3625 | 3555 | 3450 |
| 160               | 10890        | 6890  | 5940     | 5365 | 5200 | 5035 | 4950        | 4870 | 4745 | 4620 | 4455 | 4330 | 4250 | 4125 |
| 200               | 11880        | 7515  | 6480     | 5850 | 5670 | 5490 | 5400        | 5310 | 5175 | 5040 | 4860 | 4725 | 4635 | 4500 |
| 240               | 12870        | 8140  | 7020     | 6340 | 6145 | 5950 | 5850        | 5755 | 5605 | 5460 | 5265 | 5120 | 5020 | 4875 |
| 280               | 13990        | 8850  | 7630     | 6890 | 6680 | 6465 | 6360        | 6255 | 6095 | 5935 | 5725 | 5565 | 5460 | 5300 |
| 320               | 15840        | 10020 | 8640     | 7800 | 7560 | 7320 | 7200        | 7080 | 6900 | 6720 | 6480 | 6300 | 6180 | 6000 |

#### Cyclic load

| Pressure<br>(kPa) | Speed (km/h) |       |          |      |      |      |             |      |      |      |      |      |      |      |
|-------------------|--------------|-------|----------|------|------|------|-------------|------|------|------|------|------|------|------|
|                   | 0            | 5     | 10<br>LT | 15   | 20   | 25   | 30<br>10 HT | 35   | 40   | 45   | 50   | 55   | 60   | 65   |
| 80                | 6995         | 5090  | 4585     | 4080 | 3765 | 3390 | 3260        | 3155 | 3050 | 2970 | 2860 | 2785 | 2730 | 2650 |
| 120               | 9110         | 6625  | 5970     | 5315 | 4900 | 4415 | 4245        | 4105 | 3970 | 3865 | 3725 | 3625 | 3555 | 3450 |
| 160               | 10890        | 7920  | 7135     | 6355 | 5860 | 5280 | 5075        | 4910 | 4745 | 4620 | 4455 | 4330 | 4250 | 4125 |
| 200               | 11880        | 8640  | 7785     | 6930 | 6390 | 5760 | 5535        | 5355 | 5175 | 5040 | 4860 | 4725 | 4635 | 4500 |
| 240               | 12870        | 9360  | 8435     | 7510 | 6925 | 6240 | 5995        | 5800 | 5605 | 5460 | 5265 | 5120 | 5020 | 4875 |
| 280               | 13990        | 10175 | 9170     | 8160 | 7525 | 6785 | 6520        | 6305 | 6095 | 5935 | 5725 | 5565 | 5460 | 5300 |
| 320               | 15840        | 11520 | 10380    | 9240 | 8520 | 7680 | 7380        | 7140 | 6900 | 6720 | 6480 | 6300 | 6180 | 6000 |

## TIRE DIMENSIONS

|                          | New tire | Max. in service |
|--------------------------|----------|-----------------|
| OVERALL DIAMETER         | 1810 mm  | 1845 mm         |
| TIRE WIDTH               | 620 mm   | 677 mm          |
| PATTERN DEPTH            | 33 mm    |                 |
| PATTERN DEPTH ON TIE BAR | 28 mm    |                 |
| MAX. INFLATION PRESSURE  | 320 kPa  |                 |

|                               |                                                                                                              |
|-------------------------------|--------------------------------------------------------------------------------------------------------------|
| STATIC LOADED RADIUS          | 819 mm @ 6900 kg / 320 kPa                                                                                   |
| DYNAMIC ROLLING CIRCUMFERENCE | 5510 mm @ 6900 kg / 320 kPa                                                                                  |
| DYNAMIC ROLLING RADIUS        | 877 mm @ 6900 kg / 320 kPa                                                                                   |
| SPEED RADIUS INDEX            | 875                                                                                                          |
| TUBELESS VALVE                | TR618A                                                                                                       |
| BELT MATERIAL                 | Steel                                                                                                        |
| MARKINGS                      | M+S                                                                                                          |
| STUDDABLE                     | Yes<br>Marked stud positions on tread<br>Number of studs 192 pcs<br>Recommended stud 12-20,12-23,12-24,16-19 |
| VOLUME                        | 865 l 100%<br>649 l 75%                                                                                      |

## WATER AND SALT BALLASTING

(CaCl<sub>2</sub>, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% |         | Water filling 75% |         | Water/salt filling (75% / -30°C) |         |      |     | Total weight increase |      |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|------|
|                  |         |                   |         | Water                            |         | Salt |     |                       |      |
| Litres           | Gallons | Litres            | Gallons | Litres                           | Gallons | kg   | lbs | kg                    | lbs  |
| 865              | 229     | 649               | 171     | 532                              | 141     | 271  | 598 | 803                   | 1770 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)