

600/70R30 165D/161E NOKIAN TYRES GROUND KING SB TL

A crossover tire for mixed agricultural work

PRODUCT CODE	T445726
TIRE CLASSIFICATION CODE	R-1W
APPLICATION	Tractor
LI / SPEED SYMBOL	165D (161E)
RIM RECOMMENDED	DW20B
RIM PERMITTED	DW18L
TYPE APPROVAL	E8 106R-001796



LOAD CAPACITY FOR TRACTOR, LB

Tractor

Pressure (psi)	Speed (mph)													
	2.5	5	10	12	15	17.5	22.5	25	27.5	30	35	37.5	40	42.5
12	8840	7805	6965	6405	6160	5985	5830	5700	5565	5465	5355	5280	5205	4740
17	11245	9920	8865	8135	7835	7605	7410	7240	7075	6945	6810	6715	6615	6020
23	13680	12070	10780	9900	9535	9260	9015	8805	8610	8455	8290	8170	8045	7320
29	14990	13230	11815	10845	10450	10140	9875	9655	9435	9260	9085	8950	8820	8025
35	15930	14055	12555	11530	11100	10780	10495	10265	10030	9845	9655	9515	9370	8530
41	17800	15710	14030	12885	12410	12050	11730	11465	11210	11000	10790	10625	10470	9535
46	19300	17030	15210	13965	13460	13060	12720	12435	12145	11925	11695	11520	11355	10330

Increase the inflation pressure by 40 kPa (0,4 bar , 7 psi) for : Extensive road driving and use on slopes with inclination more than 20%. Do not exceed maximum pressure. In dual formation the load capacity is 0,88 x single tire load capacity per tire. For high torque field application use 30km/h line.

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	62.5 in	64.4 in
TIRE WIDTH	23.6 in	24.8 in
PATTERN DEPTH	69/32 in	
MAX. INFLATION PRESSURE	46 psi	

STATIC LOADED RADIUS	28.1 in @ 11400 lb / 46 psi
DYNAMIC ROLLING CIRCUMFERENCE	189.8 in @ 11400 lb / 46 psi
DYNAMIC ROLLING RADIUS	30.2 in @ 11400 lb / 46 psi
SPEED RADIUS INDEX	750
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
MARKINGS	M+S
STUDDABLE	Yes Marked stud positions on tread Number of studs 144 pcs Recommended stud 12-20,12-23-12-24,16-19
VOLUME	154 gallons 100% 116 gallons 75%

WATER AND SALT BALLASTING

(CaCl2, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
584	154	438	116	359	95	183	404	542	1195

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/