

VF540/65R28 157D/154E NOKIAN TYRES SOIL KING VF SB TL

Next level efficiency for high-power tractors in farming

PRODUCT CODE CH445885

TIRE CLASSIFICATION CODE R-1W

LI / SPEED SYMBOL 157D (154E)



TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER		
TIRE WIDTH		
PATTERN DEPTH		
PATTERN DEPTH ON TIE BAR		
MAX. INFLATION PRESSURE		

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
0		0	0	0	0	0	0	0	0

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/