

VF650/65R38 172D/169E NOKIAN TYRES SOIL KING VF SB TL

Next level efficiency for high-power tractors in farming

PRODUCT CODE	T445884
TIRE CLASSIFICATION CODE	R-1W
APPLICATION	Tractor
LI / SPEED SYMBOL	172D (169E)
RIM RECOMMENDED	DW23B
RIM PERMITTED	DW21B, DW20B
TYPE APPROVAL	E4 106R-006640



LOAD CAPACITY FOR TRACTOR, KG

Pressure (kPa)	Speed (km/h)													
	0	5	10	15	20	25	30	35	40	50	55	60	65	70
60	7475	4030	3575	3415	3380	3350	3315	3285	3250	3250	3250	3250	3250	2960
80	8625	4650	4125	3940	3900	3865	3825	3790	3750	3750	3750	3750	3750	3415
100	9775	5270	4675	4465	4420	4380	4335	4295	4250	4250	4250	4250	4250	3870
120	11215	6045	5365	5120	5070	5020	4975	4925	4875	4875	4875	4875	4875	4435
140	12190	6570	5830	5565	5510	5460	5405	5355	5300	5300	5300	5300	5300	4825
160	13340	7190	6380	6090	6030	5975	5915	5860	5800	5800	5800	5800	5800	5280
180	13800	7440	6600	6300	6240	6180	6120	6060	6000	6000	6000	6000	6000	5460
200	14490	7810	6930	6615	6550	6490	6425	6365	6300	6300	6300	6300	6300	5735

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1835 mm	1845 mm
TIRE WIDTH	658 mm	683 mm
PATTERN DEPTH	59 mm	
PATTERN DEPTH ON TIE BAR		
MAX. INFLATION PRESSURE	280 kPa	

STATIC LOADED RADIUS	823 mm @ 6300 kg / 200 kPa
DYNAMIC ROLLING CIRCUMFERENCE	5509 mm @ 6300 kg / 200 kPa
DYNAMIC ROLLING RADIUS	877 mm @ 6300 kg / 200 kPa
SPEED RADIUS INDEX	875
TUBELESS VALVE	TR618A
BELT MATERIAL	Steel
STUDDABLE	Yes Marked stud positions on tread Number of studs 120 pcs Recommended stud 12-20,12-23-12-24,16-19
VOLUME	847 l 100% 635 l 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
847	224	635	168	521	138	266	586	787	1735

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/