

## 285/70R19.5 145/143M NOKIAN TYRES E-TRUCK DRIVE

A sturdy drive axle tire for medium-sized trucks in regional and urban traffic

PRODUCT CODE	T675264
APPLICATION	Drive
LI / SPEED SYMBOL	145/143M
RIM RECOMMENDED	8.25
RIM PERMITTED	9.00
TYPE APPROVAL	E4 0043515, E4 029281 S2WR2



### LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		600	625	650	675	700	725	750	775	800	825	850
Single	130	4390	4540	4680	4820	4970	5110	5250	5390	5530	5660	5800
Dual	130	8250	8520	8790	9060	9330	9600	9860	10120	10380	10640	10900

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

### TIRE DIMENSIONS

OVERALL DIAMETER	889 mm
TIRE WIDTH	270 mm
STATIC LOADED RADIUS	410 mm
ROLLING CIRCUMFERENCE	2702 mm
MIN. DUAL SPACING	318 mm
PATTERN DEPTH	14.3 mm

### EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	C
NOISE	73 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)