

215/75R17.5 126/124M NOKIAN TYRES E-TRUCK DRIVE

A sturdy tire for drive axle in regional and urban traffic

PRODUCT CODE	T675337
APPLICATION	Drive
LI / SPEED SYMBOL	126/124M
RIM RECOMMENDED	6.00
RIM PERMITTED	6.75
TYPE APPROVAL	E4 0059141, E4 0414988 S2W2R3B



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)								
		73	76	80	83	87	91	94	98	102
Single	80	5730	5950	6175	6395	6635	6855	7055	7275	7495
Dual	80	10780	11200	11640	12060	12480	12895	13295	13715	14110

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	30.5 in
TIRE WIDTH	8.2 in
STATIC LOADED RADIUS	14.2 in
ROLLING CIRCUMFERENCE	93.2 in
MIN. DUAL SPACING	9.4 in
PATTERN DEPTH	18/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	74 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/