

## 235/75R17.5 132/130M NOKIAN TYRES E-TRUCK DRIVE

A sturdy tire for drive axle in regional and urban traffic

PRODUCT CODE	T675339
APPLICATION	Drive
LI / SPEED SYMBOL	132/130M
RIM RECOMMENDED	6.75
RIM PERMITTED	7.50
TYPE APPROVAL	E4 0059143, E4 0414988 S2W2R3B



### LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)									
		80	83	87	91	94	98	102	105	109	112
Single	80	6700	6945	7185	7430	7650	7895	8135	8355	8600	8820
Dual	80	12745	13205	13645	14110	14550	14990	15455	15895	16315	16755

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

### TIRE DIMENSIONS

OVERALL DIAMETER	31.5 in
TIRE WIDTH	9 in
STATIC LOADED RADIUS	14.6 in
ROLLING CIRCUMFERENCE	96.3 in
MIN. DUAL SPACING	10.3 in
PATTERN DEPTH	18/32 in

### EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	74 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)