

## 265/70R19.5 140/138M NOKIAN TYRES E-TRUCK DRIVE

A sturdy drive axle tire for medium-sized trucks in regional and urban traffic

PRODUCT CODE	T675340
APPLICATION	Drive
LI / SPEED SYMBOL	140/138M
RIM RECOMMENDED	7.50
RIM PERMITTED	6.75, 8.25
TYPE APPROVAL	E4 0059145, E4 0414988 S2W2R3B



### LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)									
		80	83	87	91	94	98	102	105	109	112
Single	80	8380	8685	8975	9280	9570	9875	10165	10450	10735	11025
Dual	80	15805	16380	16955	17525	18080	18630	19180	19730	20285	20810

### TIRE DIMENSIONS

OVERALL DIAMETER	34.1 in
TIRE WIDTH	10.2 in
STATIC LOADED RADIUS	15.8 in
ROLLING CIRCUMFERENCE	104.4 in
MIN. DUAL SPACING	11.6 in
PATTERN DEPTH	19/32 in

### EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	74 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)