

315/70R22.5 154/150L NOKIAN TYRES E-TRUCK DRIVE

Reliable all-season tyres for medium and regional haul transport.

PRODUCT CODE	T675367
APPLICATION	Drive
LI / SPEED SYMBOL	154/150L
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0054834, E4 0414988 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	120	5780	5960	6130	6310	6480	6650	6830	7000	7160	7330	7500
Dual	120	10330	10650	10960	11270	11580	11890	12200	12500	12800	13100	13400

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	1022 mm
TIRE WIDTH	308 mm
STATIC LOADED RADIUS	474 mm
ROLLING CIRCUMFERENCE	3117 mm
MIN. DUAL SPACING	351 mm
PATTERN DEPTH	19.5 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	74 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/