

# 315/80R22.5 154/150M NOKIAN TYRES E-TRUCK DRIVE

Reliable all-season tyres for medium and regional haul transport.

PRODUCT CODE	T675280
APPLICATION	Drive
LI / SPEED SYMBOL	154/150M (156/150L)
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0036129, E4 029281 S2WR2



## LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)							
		650	675	700	725	750	775	800	825
Single	130	6200	6390	6580	6760	6950	7130	7320	7500
Dual	130	11070	11410	11750	12080	12420	12750	13070	13400

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	120	6450	6650	6850	7040	7240	7430	7620	7810	8000
Dual	120	11070	11410	11750	12080	12420	12750	13070	13400	

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

## TIRE DIMENSIONS

OVERALL DIAMETER	1076 mm
TIRE WIDTH	314 mm
STATIC LOADED RADIUS	502 mm
ROLLING CIRCUMFERENCE	3286 mm
MIN. DUAL SPACING	351 mm
PATTERN DEPTH	17.5 mm

## EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	C
NOISE	76 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)