

265/70R19.5 140/138M NOKIAN TYRES E-TRUCK STEER

A sturdy steer axle tire for medium-sized trucks in regional and urban traffic

PRODUCT CODE	T675343
APPLICATION	Steer
LI / SPEED SYMBOL	140/138M
RIM RECOMMENDED	7.50
RIM PERMITTED	6.75, 8.25
TYPE APPROVAL	E4 0059145, E4 0414987 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)									
		550	575	600	625	650	675	700	725	750	775
Single	130	3800	3940	4070	4210	4340	4480	4610	4740	4870	5000
Dual	130	7170	7430	7690	7950	8200	8450	8700	8950	9200	9440

TIRE DIMENSIONS

STATIC LOADED RADIUS	399 mm
ROLLING CIRCUMFERENCE	2638 mm
MIN. DUAL SPACING	295 mm
PATTERN DEPTH	13 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/