

285/70R19.5 146/144L NOKIAN TYRES E-TRUCK STEER

A sturdy steer axle tire for medium-sized trucks in regional and urban traffic

PRODUCT CODE	T675344
APPLICATION	Steer
LI / SPEED SYMBOL	146/144L
RIM RECOMMENDED	8.25
RIM PERMITTED	9.00
TYPE APPROVAL	E4 0059147, E4 0414987 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)												
		600	625	650	675	700	725	750	775	800	825	850	875	900
Single	120	4340	4480	4620	4770	4910	5050	5190	5320	5460	5600	5730	5870	6000
Dual	120	8100	8370	8630	8900	9160	9420	9680	9940	10190	10450	10700	10950	11200

TIRE DIMENSIONS

OVERALL DIAMETER	895 mm
TIRE WIDTH	278 mm
STATIC LOADED RADIUS	415 mm
ROLLING CIRCUMFERENCE	2739 mm
MIN. DUAL SPACING	318 mm
PATTERN DEPTH	13.5 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/