

## 285/70R19.5 146/144L NOKIAN TYRES E-TRUCK STEER

A sturdy steer axle tire for medium-sized trucks in regional and urban traffic

PRODUCT CODE	T675344
APPLICATION	Steer
LI / SPEED SYMBOL	146/144L
RIM RECOMMENDED	8.25
RIM PERMITTED	9.00
TYPE APPROVAL	E4 0059147, E4 0414987 S2W2R3B



### LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)												
		87	91	94	98	102	105	109	112	116	120	123	127	131
Single	75	9570	9875	10185	10515	10825	11135	11440	11730	12035	12345	12630	12940	13230
Dual	75	17855	18455	19025	19620	20195	20770	21340	21915	22465	23040	23590	24140	24690

### TIRE DIMENSIONS

OVERALL DIAMETER	35.2 in
TIRE WIDTH	10.9 in
STATIC LOADED RADIUS	16.3 in
ROLLING CIRCUMFERENCE	107.8 in
MIN. DUAL SPACING	12.5 in
PATTERN DEPTH	17/32 in

### EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)