

# 295/80R22.5 154/149M NOKIAN TYRES E-TRUCK STEER

## Steady handling in the long run

PRODUCT CODE	T675336
APPLICATION	Steer
LI / SPEED SYMBOL	154/149M
RIM RECOMMENDED	9.00
RIM PERMITTED	8.25
TYPE APPROVAL	E4 0059139, E4 0414987 S2W2R3B



## LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	130	6050	6240	6420	6600	6790	6970	7140	7320	7500
Dual	130	10490	10810	11130	11450	11760	12070	12380	12690	13000

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

## TIRE DIMENSIONS

OVERALL DIAMETER	1050 mm
TIRE WIDTH	303 mm
STATIC LOADED RADIUS	458 mm
ROLLING CIRCUMFERENCE	3212 mm
MIN. DUAL SPACING	335 mm
PATTERN DEPTH	14.5 mm

## EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)