

# 315/70R22.5 154/150L NOKIAN TYRES E-TRUCK STEER

Steady handling in the long run

PRODUCT CODE	T675223
APPLICATION	Steer
LI / SPEED SYMBOL	154/150L (152/148M)
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0038372, E4 0210252 S2WR2



## LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	75	12745	13140	13515	13910	14285	14660	15060	15430	15785	16160	16535
Dual	75	22775	23480	24165	24845	25530	26215	26895	27560	28220	28880	29540

Axle fitting	Speed (mph)	Pressure (psi)									
		94	98	102	105	109	112	116	120	123	
Single	80	12630	13005	13405	13780	14155	14530	14905	15280	15655	
Dual	80	22420	23105	23790	24450	25135	25795	26455	27115	27780	

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

## TIRE DIMENSIONS

OVERALL DIAMETER	40.1 in
TIRE WIDTH	12.5 in
STATIC LOADED RADIUS	18.6 in
ROLLING CIRCUMFERENCE	121.9 in
MIN. DUAL SPACING	13.8 in
PATTERN DEPTH	17/32 in

## EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	A
NOISE	70 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)