

245/70R17.5 143/141J NOKIAN TYRES E-TRUCK TRAILER

Reliable all-season tires for long and medium haul

PRODUCT CODE	T675328
APPLICATION	Trailer
LI / SPEED SYMBOL	143/141J (146/146F)
RIM RECOMMENDED	7.50
RIM PERMITTED	6.75
TYPE APPROVAL	E4 0059150, E4 0417153 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	100	4200	4330	4460	4580	4710	4840	4960	5080	5210	5330	5450
Dual	100	7940	8180	8420	8660	8900	9140	9370	9610	9840	10070	10300

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	80	4620	4770	4910	5050	5190	5320	5460	5600	5730	5870	6000
Dual	80	9250	9530	9810	10090	10370	10650	10920	11190	11460	11730	12000

TIRE DIMENSIONS

OVERALL DIAMETER	792 mm
TIRE WIDTH	243 mm
STATIC LOADED RADIUS	363 mm
ROLLING CIRCUMFERENCE	2424 mm
MIN. DUAL SPACING	279 mm
PATTERN DEPTH	13 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	69 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/