

# 385/65R22.5 160K NOKIAN TYRES E-TRUCK TRAILER

Reliable all-season tires for long and medium haul

PRODUCT CODE	T675283
APPLICATION	Trailer
LI / SPEED SYMBOL	160K (158L)
RIM RECOMMENDED	11.75
RIM PERMITTED	12.25
TYPE APPROVAL	E4 0036130, E4 028996 S2WR2



## LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	67.5	15300	15765	16225	16690	17150	17615	18055	18495	18960	19400	19840

Axle fitting	Speed (mph)	Pressure (psi)									
		94	98	102	105	109	112	116	120	123	
Single	75	15125	15585	16050	16490	16955	17395	17855	18300	18740	

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

## TIRE DIMENSIONS

OVERALL DIAMETER	42.5 in
TIRE WIDTH	14.9 in
STATIC LOADED RADIUS	19.6 in
ROLLING CIRCUMFERENCE	129.3 in
PATTERN DEPTH	20/32 in

## EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	68 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)