

275/70R22.5 152/149J NOKIAN TYRES HAKKA CITY BUS

All-weather tire for all axles – durability and all-weather performance for city buses

PRODUCT CODE	T675318
APPLICATION	Steer / Drive
LI / SPEED SYMBOL	152/149J (150/148K)
RIM RECOMMENDED	8.25
RIM PERMITTED	7.50
TYPE APPROVAL	E4 0058466, E4 0416941 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	100	5470	5640	5810	5970	6140	6300	6460	6620	6780	6940	7100
Dual	100	10020	10330	10630	10940	11240	11530	11830	12130	12420	12710	13000

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	110	5160	5320	5480	5640	5790	5940	6100	6250	6400	6550	6700
Dual	110	9710	10010	10310	10600	10890	11180	11470	11750	12040	12320	12600

TIRE DIMENSIONS

STATIC LOADED RADIUS	448 mm
ROLLING CIRCUMFERENCE	2922 mm
MIN. DUAL SPACING	311 mm
PATTERN DEPTH	18.5 mm

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/