

295/80R22.5 154/150M NOKIAN TYRES HAKKA TRUCK COACH

Coach tire with confident grip and comfort in every axle position

PRODUCT CODE	T675355
APPLICATION	Steer / Drive
LI / SPEED SYMBOL	154/150M
RIM RECOMMENDED	9.00
RIM PERMITTED	8.25
TYPE APPROVAL	E4 0058684, E4 0416952 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	130	6050	6240	6420	6600	6790	6970	7140	7320	7500
Dual	130	10810	11140	11470	11800	12120	12450	12770	13080	13400

TIRE DIMENSIONS

OVERALL DIAMETER	1055 mm
TIRE WIDTH	303 mm
STATIC LOADED RADIUS	490 mm
ROLLING CIRCUMFERENCE	3184 mm
MIN. DUAL SPACING	335 mm
PATTERN DEPTH	15.5 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	A
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/