

295/80R22.5 154/150M NOKIAN TYRES HAKKA TRUCK COACH

Coach tire with confident grip and comfort in every axle position

PRODUCT CODE	T675355
APPLICATION	Steer / Drive
LI / SPEED SYMBOL	154/150M
RIM RECOMMENDED	9.00
RIM PERMITTED	8.25
TYPE APPROVAL	E4 0058684, E4 0416952 S2W2R3B



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)								
		94	98	102	105	109	112	116	120	123
Single	80	13340	13755	14155	14550	14970	15365	15740	16140	16535
Dual	80	23830	24560	25285	26015	26720	27450	28155	28835	29540

TIRE DIMENSIONS

STATIC LOADED RADIUS	19.3 in
ROLLING CIRCUMFERENCE	125.4 in
MIN. DUAL SPACING	13.2 in
PATTERN DEPTH	20/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	A
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/