

295/80R22.5 154/149M NOKIAN TYRES HAKKA TRUCK COACH

Coach tire with confident grip and comfort in every axle position

PRODUCT CODE	T675271
APPLICATION	Steer / Drive
LI / SPEED SYMBOL	154/149M
RIM RECOMMENDED	9.00
RIM PERMITTED	8.25
TYPE APPROVAL	E4 0048535, E4 0212617 S2WR2



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)								
		94	98	102	105	109	112	116	120	123
Single	80	13340	13755	14155	14550	14970	15365	15740	16140	16535
Dual	80	23125	23830	24535	25245	25925	26610	27295	27975	28660

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	41.5 in
TIRE WIDTH	11.7 in
STATIC LOADED RADIUS	19.3 in
ROLLING CIRCUMFERENCE	126.3 in
MIN. DUAL SPACING	13.2 in
PATTERN DEPTH	20/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	C
NOISE	70 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/