

295/60R22.5 150/147L NOKIAN TYRES HAKKA TRUCK DRIVE 2

Enhanced grip and even wear for long distance and regional transport

PRODUCT CODE	T675324
APPLICATION	Drive
LI / SPEED SYMBOL	150/147L
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0058478, E4 0416943 S2W2R3B



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	120	5160	5320	5480	5640	5790	5940	6100	6250	6400	6550	6700
Dual	120	9480	9770	10060	10350	10630	10910	11190	11470	11750	12030	12300

TIRE DIMENSIONS

STATIC LOADED RADIUS	429 mm
ROLLING CIRCUMFERENCE	2806 mm
MIN. DUAL SPACING	329 mm
PATTERN DEPTH	17 mm

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	A
NOISE	73 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/