

295/60R22.5 150/147L NOKIAN TYRES HAKKA TRUCK DRIVE 2

Improved mileage and stability for long distance and regional transport

PRODUCT CODE	T675324
APPLICATION	Drive
LI / SPEED SYMBOL	150/147L
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0058478, E4 0416943 S2W2R3B



LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	98	102	105	109	112	116	120	123	127	131
Single	75	11375	11730	12080	12435	12765	13095	13450	13780	14110	14440	14770
Dual	75	20900	21540	22180	22820	23435	24050	24670	25285	25905	26520	27115

TIRE DIMENSIONS

STATIC LOADED RADIUS	16.9 in
ROLLING CIRCUMFERENCE	110.5 in
MIN. DUAL SPACING	13 in
PATTERN DEPTH	21/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	A
NOISE	73 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/