315/80R22.5 156/150L NOKIAN TYRES HAKKA TRUCK DRIVE 2

Enhanced grip and even wear for long distance and regional transport

PRODUCT CODE	T675350
APPLICATION	Drive
LI / SPEED SYMBOL	156/150L (154/150M)
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0054013, E4 0416943 S2W2R3B

LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	**675**	**700**	**725**	**750**	**775**	**800**	**825**	**850**
Single	120	6450	6650	6850	7040	7240	7430	7620	7810	8000
Dual	120	10810	11140	11470	11800	12120	12450	12770	13080	13400

Axle fitting	Speed (km/h)	Pressure (kPa)							
		650	**675**	**700**	**725**	**750**	**775**	**800**	**825**
Single	130	6200	6390	6580	6760	6950	7130	7320	7500
Dual	130	11070	11410	11750	12080	12420	12750	13070	13400

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	1092 mm
TIRE WIDTH	314 mm
STATIC LOADED RADIUS	506 mm
ROLLING CIRCUMFERENCE	3282 mm
MIN. DUAL SPACING	351 mm
PATTERN DEPTH	18.5 mm

EU-LABEL VALUES

ROLLING RESISTANCE	D
WET GRIP	B
NOISE	73 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:
- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/