

315/60R22.5 152/148L NOKIAN TYRES HAKKA TRUCK DRIVE

Grip around the year

PRODUCT CODE	T675251
APPLICATION	Drive
LI / SPEED SYMBOL	152/148L
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0044086, E4 0211773 S2WR2



LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)										
		650	675	700	725	750	775	800	825	850	875	900
Single	120	5470	5640	5810	5970	6140	6300	6460	6620	6780	6940	7100
Dual	120	9710	10010	10310	10600	10890	11180	11470	11750	12040	12320	12600

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	963 mm
TIRE WIDTH	311 mm
STATIC LOADED RADIUS	450 mm
ROLLING CIRCUMFERENCE	2927 mm
MIN. DUAL SPACING	344 mm
PATTERN DEPTH	15.5 mm

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	C
NOISE	76 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Traction, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/