315/60R22.5 154/148L NOKIAN TYRES HAKKA TRUCK STEER

Stable steering tire for all seasons

PRODUCT CODE	T675249
APPLICATION	Steer
LI / SPEED SYMBOL	154/148L
RIM RECOMMENDED	9.00
RIM PERMITTED	9.75
TYPE APPROVAL	E4 0044466, E4 028997 S2WR2

LOAD CAPACITY, LB

Axle fitting	Speed (mph)	Pressure (psi)										
		94	**98**	**102**	**105**	**109**	**112**	**116**	**120**	**123**	**127**	**131**
Dual	75	21405	22070	22730	23370	24010	24650	25285	25905	26545	27160	27780
Single	75	12745	13140	13515	13910	14285	14660	15060	15430	15785	16160	16535

Note! The inflation pressures given in the table are minimum values. It is recommended to use 0.5-1.0 bar higher values to compensate the effect of temperature variation and possible pressure gauge error, but not more than 9.0 bar should be used.

TIRE DIMENSIONS

OVERALL DIAMETER	37.8 in
TIRE WIDTH	12.4 in
STATIC LOADED RADIUS	17.7 in
ROLLING CIRCUMFERENCE	114.8 in
MIN. DUAL SPACING	13.5 in
PATTERN DEPTH	16/32 in

EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	B
NOISE	72 dB
NOISE WAVES	B
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:
- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/