

# 265/70R19.5 143/141J NOKIAN TYRES HAKKA TRUCK TRAILER 2

Improved mileage and stability for long distance and regional transport

PRODUCT CODE	T675352
APPLICATION	Trailer
LI / SPEED SYMBOL	143/141J
RIM RECOMMENDED	7.50
RIM PERMITTED	6.75, 8.25
TYPE APPROVAL	E4 0054011, E4 0416947 S2W2R3B



## LOAD CAPACITY, KG

Axle fitting	Speed (km/h)	Pressure (kPa)								
		650	675	700	725	750	775	800	825	850
Single	100	4400	4530	4670	4800	4930	5060	5190	5320	5450
Dual	100	8310	8570	8820	9070	9320	9570	9810	10060	10300

## TIRE DIMENSIONS

OVERALL DIAMETER	871 mm
TIRE WIDTH	260 mm
STATIC LOADED RADIUS	404 mm
ROLLING CIRCUMFERENCE	2601 mm
MIN. DUAL SPACING	295 mm
PATTERN DEPTH	14.5 mm

## EU-LABEL VALUES

ROLLING RESISTANCE	C
WET GRIP	A
NOISE	71 dB
NOISE WAVES	A
MARKINGS	M+S, SnowGrip, Regroovable

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

The tire has been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: [www.nokiantyres.com/heavy/technical-tire-manual/](http://www.nokiantyres.com/heavy/technical-tire-manual/)